


Geberit PE luk sa dugim krakom



Primer slike



NAMENE

- Za odvodnju otpadnih voda zgrade

PREDNOSTI

- Veliki radijus

- Otporno na UV zračenje

TEHNIČKI PODACI

Materijal proizvoda

PE-HD

INFO

- Geberit PE kolena sa uglovima od 15°, 30°, 45° i 88.5° mogu da se zavare na oba kraka pomoću Geberit elektrovarnih spojnica
- Geberit PE koleno sa uglom od 90° može da se zavari na dugom kraku pomoću Geberit elektrovarnih spojnica

Br. art.	DN	d, ø mm	arc °	X1 cm	X2 cm	K1 maks. cm	K2 maks. cm	r cm
367.046.16.1	100	110	45	14.7	6	11	2.5	
379.055.16.1	30	32	90	10	3	7		3
360.055.16.1	40	40	90	15	3	12		3
361.055.16.1	50	50	90	18	4	14		4
363.055.16.1	56	56	90	21	4	17		4

<i>Br. art.</i>	<i>DN</i>	<i>d, ø mm</i>	<i>arc °</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>K1 maks. cm</i>	<i>K2 maks. cm</i>	<i>r cm</i>
364.055.16.1	60	63	90	21	5	16		5
365.055.16.1	70	75	90	21	7	14		7
366.055.16.1	90	90	90	24	9	15		9
367.055.16.1	100	110	90	27	10	17		10
368.055.16.1	125	125	90	20	11	9		11
369.055.16.1	150	160	90	20	14	6		14