



Primer slike

NAMENE

- Za odvodnju odpadnih voda zgrade

PREDNOSTI

- Plastificirano

TEHNIČKI PODACI

Materijal proizvoda

Čelik

DODATNO ZA PORUČIVANJE

- Geberit PE prirubnička zaptivka

Br. art.	DN	d, ø mm	D cm	k mm	m mm	H cm	n kom.	PN bar
361.748.00.1	50	50	15	110	18	1.2	4	10
363.748.00.1	56 / 60	56 / 63	16.5	125	18	1.2	4	10
365.748.00.1	70	75	18.5	145	18	1.2	4	10
366.748.00.1	90	90	20	160	18	1.4	8	10
367.748.00.1	100	110	22	180	18	1.4	8	10

<i>Br. art.</i>	<i>DN</i>	<i>d_ø</i> mm	<i>D</i> cm	<i>k</i> mm	<i>m</i> mm	<i>H</i> cm	<i>n</i> kom.	<i>PN</i> bar
368.748.00.1	125	125	25	210	18	1.4	8	10
369.748.00.1	150	160	28.5	240	23	1.4	8	10
370.748.00.1	200	200	34	295	23	1.4	8	3.2
371.748.00.1	250	250	39.5	350	23	1.6	12	3.2
372.748.00.1	300	315	44.5	400	23	2	12	3.2