



DA ETIMAT 10 230V AC/DC

Shunt trip release

ETI Code:	002159301
Rated AC voltage:	230 V
DC rated control supply voltage U_c :	230 V
Rated DC voltage:	230 V
Catalogue Group:	Accessories ETIMAT 6/10
Function accessories:	Shunt trip release
Application:	EN 60715
Function:	Shunt trip release
Rated Frequency:	50/60 Hz
Rated cross section:	1-25 mm ²
Max. inrush current:	3.6 A
Standards:	EN 60715
To use with:	ETIMAT 6

Online product page [🔗](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Voltage type	AC/DC
Voltage type for actuating	AC/DC
Device fitting	Miniature circuit breaker (MCB)
Rated control supply voltage DC(Min)	230 V
Rated control supply voltage AC 50 Hz(Max)	230 V
Rated control supply voltage AC 50 Hz(Min)	230 V
Rated voltage	230 V
Rated control supply voltage DC(Max)	230 V
Function	Remote release
Type of electric connection	Screw connection
Width in number of modular spacings	1

Logistics

Product

Net depth	72.92 mm
Net weight of the product	0.103 kg
Net width	18 mm
Net height	87.2 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895308553
Basic packaging weight	0.119 kg
Basic Packaging Dimensions Depth	0.037 m
Basic Packaging Dimensions Height	0.075 m
Basic packaging volume	0 m ³
Basic Packaging Dimensions Width	0.09 m
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	6.776 kg
Transport packaging volume	0.017 m ³
Transport packaging quantity	54 pcs
Customs tariff	85389099
Transport Packaging Dimensions Height	0.25 m
Transport Packaging Dimensions Width	0.235 m
Transport Packaging Dimensions Depth	0.295 m
EAN code for a transport packaging	3838895308560
Pallet quantity	2,808 pcs

Dimension

