

t-2P+Z Schuko P

Socket



ETI Code:	002414020
Color:	Grey
Rated DC voltage:	24 V
Standards:	IEC/EN 60947-1, IEC/EN 60947-3
Max input cross-section:	6 mm ²
Utilization category:	AC-22A
Rated Frequency:	50/60 Hz
Application:	IEC/EN 60947-1, IEC/EN 60947-3
Catalogue Group:	DIN sockets
Catalogue Subgroup:	Schuko
Function:	DIN socket
Rated current:	16 A

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Type of fastening	Snap mounting (engagement)
Device depth	65 mm
Nominal current	16 A
Model	Socket outlet CEE 7/3 (type F)
Frequency(Min)	50 Hz
Mounting method	Other
Device height	90 mm
Nominal voltage	250 V
Frequency(Max)	60
Halogen free	Yes
Number of units	1
Colour	Grey
Device width	45 mm
Suitable for degree of protection (IP)	IP20
Material	Plastic

Logistics

Product

Net depth	64.5 mm
Net weight of the product	80 g
Net width	45 mm
Net height	94 mm
Stock unit of measure	pcs
EAN code for a single product	5904722932609

Basic Packaging

EAN code for a basic packaging	5904722995956
Basic packaging weight	0.6 kg
Basic Packaging Dimensions Depth	230 mm
Basic Packaging Dimensions Height	75 mm
Basic packaging volume	1.639 dm³
Basic Packaging Dimensions Width	95 mm
Basic packaging quantity	5 pcs

Transport Packaging

Transport packaging weight	12.2 kg
Transport packaging volume	50 dm³
Transport packaging quantity	100 pcs
Customs tariff	85366990
Transport Packaging Dimensions Height	310 mm
Transport Packaging Dimensions Width	250 mm
Transport Packaging Dimensions Depth	510 mm
EAN code for a transport packaging	5904722995963
Pallet quantity	1,600 pcs

Dimension

