



R 25-20 230V

Modular contactor

ETI Code:	002463502
Rated operation current Ie at AC1:	25 A
Depth:	60 mm
Residual current type:	AC
IP rating:	IP40
Type description:	AC
Rated operational current Ie AC-1/AC-7:	25 A
Rated operational voltage (AC):	440 V
Rated control circuit voltage Uc (AC):	230 V
Type (Legacy):	AC
Rated Frequency:	50/60 Hz
No. of NO contacts:	2
Function:	Modular contactor
Type of Installation:	DIN rail
Catalogue Group:	R

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Additional equipment possible	Yes
Voltage type (excitation voltage)	AC
Built-in depth	60 mm
Rated excitation voltage(Min)	230 V
Rated operating voltage(Max)	230 V
Max. load fluorescent lamp	1,190 VA
Voltage type (operating voltage)	AC/DC
Degree of protection (IP)	IP20
Max. load fluorescent lamp (parallel compensated)	1,360 VA
Utilization category according to EN IEC 60947-4-1	AC-1
Rated excitation voltage(Max)	230 V
Max. load fluorescent lamp (Duo circuit)	2,552 VA
Rated operating voltage(Min)	24 V
Number of contacts as normally open contact	2
Rated operation current	25 A
Max. incandescent lamp load	3,000 W
Width in number of modular spacings	1

Logistics

Product

Net depth	65 mm
Net weight of the product	124.8 g
Net width	17.5 mm
Net height	88.6 mm
Stock unit of measure	pcs
EAN code for a single product	5904722988569

Basic Packaging

EAN code for a basic packaging	3838895564454
Basic packaging weight	1.56 kg
Basic Packaging Dimensions Depth	73 mm
Basic Packaging Dimensions Height	216 mm
Basic packaging volume	1.419 dm³
Basic Packaging Dimensions Width	90 mm
Basic packaging quantity	12 pcs

Transport Packaging

Transport packaging weight	15.85 kg
Transport packaging volume	16.459 dm³
Transport packaging quantity	120 pcs
Customs tariff	85364900
Transport Packaging Dimensions Height	190 mm
Transport Packaging Dimensions Width	225 mm
Transport Packaging Dimensions Depth	385 mm
EAN code for a transport packaging	3838895564461
Pallet quantity	6,360 pcs

R20
165,150

