

TER-3C

Control relay



ETI Code:	002471802
Type (Legacy):	Thermostat relay TER-3 (A,B,C)
Category:	Thermostat relay TER-3 (A,B,C)
Catalogue Group:	Temperature monitoring relays
Rated Frequency:	50 Hz
IP rating:	IP20
Type description:	Thermostat relay TER-3 (A,B,C)
Catalogue Subgroup:	Thermostat relay
Function:	Monitoring and Control relays
Supply Voltage:	24-240 V
Temperature range:	-30-70 °C
Sensor Type:	external, termistor NTC
Number of contacts:	1
Rated current:	10/16 A
Voltage type:	AC/DC
Type of contacts:	1xNO
Maximum load capacity at AC1:	4,000 VA
No. of NO contacts:	1

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



COM_ETIPRODUCT_DOCUMENTS_DESCRIPTOR



EPLAN FILE

ETIM

Rated voltage(Max)	230 V
Adjustment range comfort(Max)	70 °C
Model	Analogue
Number of channels	1
Degree of protection (IP)	IP20
Contact type	Breaker contact
Assembly depth	65 mm
Rated frequency(Min)	50 Hz
Rated frequency(Max)	50 Hz
Nominal switching current at 250 V, potential free	16 A
Rated voltage(Min)	24 V
Sensor type	Remote sensor
Adjustment range comfort(Min)	30 °C
Width in number of modular spacings	1

Logistics

Product

Net depth	64.26 mm
Net weight of the product	0.07 kg
Net width	17.5 mm
Net height	91.3 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895424246
Basic packaging weight	0.084 kg
Basic Packaging Dimensions Depth	70 mm
Basic Packaging Dimensions Height	25 mm
Basic packaging volume	0.17 dm³
Basic Packaging Dimensions Width	97 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	0.84 kg
Transport packaging volume	1.6 dm³
Transport packaging quantity	10 pcs
Customs tariff	85364900
Transport Packaging Dimensions Height	102 mm
Transport Packaging Dimensions Width	284 mm
Transport Packaging Dimensions Depth	75 mm
EAN code for a transport packaging	3838895474135
Pallet quantity	6,250 pcs

Symbol connection

