

# NH000 gG 160A/400V

## Fuse link



|                                 |                                   |
|---------------------------------|-----------------------------------|
| ETI Code:                       | 004181216                         |
| Fuse type:                      | NH                                |
| Size:                           | NH000                             |
| Rated current:                  | 160 A                             |
| Time-Current Characteristic:    | gG                                |
| Rated AC voltage:               | 400 V                             |
| Breaking capacity AC:           | 100 kA                            |
| Indicator:                      | Combination fuse status indicator |
| Power dissipation:              | 9.6 W                             |
| Operating joule integral (A2s): | 170,620                           |
| Prearcing joule integral (A2s): | 35,100                            |
| Standards:                      | IEC 60269-1, IEC 60269-2          |
| Application:                    | For cable protection              |

[Online product page](#)

## Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

## ETIM

|                                               |                                                   |
|-----------------------------------------------|---------------------------------------------------|
| Rated switching capacity AC                   | <b>120 kA</b>                                     |
| Voltage type                                  | <b>AC</b>                                         |
| Fuse construction type according to IEC 60269 | <b>NH000</b>                                      |
| Rated voltage AC                              | <b>400</b>                                        |
| Power loss at rated current                   | <b>9.6 W</b>                                      |
| Type of fuse status indicator                 | <b>Combination fuse status indicator</b>          |
| Rated current                                 | <b>160 A</b>                                      |
| Utilization category                          | <b>gG (cable protection/equipment protection)</b> |

## Logistics

### Product

|                               |               |
|-------------------------------|---------------|
| Net depth                     | 51.9 mm       |
| Net weight of the product     | 120 g         |
| Net width                     | 21 mm         |
| Net height                    | 78.6 mm       |
| Stock unit of measure         | pcs           |
| EAN code for a single product | 3838895905608 |


### Basic Packaging

|                                   |                  |
|-----------------------------------|------------------|
| EAN code for a basic packaging    | 3838895582694    |
| Basic packaging weight            | 0.373 kg         |
| Basic Packaging Dimensions Depth  | 0.084 m          |
| Basic Packaging Dimensions Height | 0.056 m          |
| Basic packaging volume            | 0 m <sup>3</sup> |
| Basic Packaging Dimensions Width  | 0.068 m          |
| Basic packaging quantity          | 3 pcs            |

### Transport Packaging

|                                       |                      |
|---------------------------------------|----------------------|
| Transport packaging weight            | 15.286 kg            |
| Transport packaging volume            | 0.018 m <sup>3</sup> |
| Transport packaging quantity          | 120 pcs              |
| Customs tariff                        | 85361090             |
| Transport Packaging Dimensions Height | 0.255 m              |
| Transport Packaging Dimensions Width  | 0.295 m              |
| Transport Packaging Dimensions Depth  | 0.235 m              |
| EAN code for a transport packaging    | 3838895582700        |
| Pallet quantity                       | 6,240 pcs            |

CutOff



Dimension

|           | A   | B  | C  | D  | E  | F   | G   | H   | I   | J  | K |       |
|-----------|-----|----|----|----|----|-----|-----|-----|-----|----|---|-------|
| NV00C     | 79  | 53 | 47 | 35 | 15 | 21  | 52  | 7,5 |     |    | 6 | kombi |
| NV00C I   | 79  | 53 | 47 | 35 | 15 | 21  | 52  | 7,5 |     |    | 6 | kombi |
| NV00      | 79  | 53 | 47 | 35 | 15 | 28  | 56  | 12  |     |    | 6 | kombi |
| NV00 I    | 79  | 53 | 47 | 35 | 15 | 28  | 56  | 12  |     |    | 6 | kombi |
| NV0       | 125 | 68 | 65 | 35 | 15 | 28  | 56  | 12  |     |    | 6 | kombi |
| NV1C      | 135 | 68 | 65 | 40 | 15 | 28  | 61  | 12  |     |    | 6 | kombi |
| NV1C I    | 135 | 68 | 65 | 40 | 15 | 28  | 61  | 12  |     |    | 6 | kombi |
| NV1       | 135 | 72 | 65 | 40 | 20 | 46  | 65  | 14  |     |    | 6 | kombi |
| NV1 I     | 135 | 72 | 65 | 40 | 20 | 46  | 65  | 14  |     |    | 6 | kombi |
| NV2C      | 150 | 72 | 65 | 48 | 20 | 46  | 73  | 14  |     |    | 6 | kombi |
| NV2C I    | 150 | 72 | 65 | 48 | 20 | 46  | 73  | 14  |     |    | 6 | kombi |
| NV2       | 150 | 72 | 65 | 48 | 26 | 54  | 73  | 14  |     |    | 6 | kombi |
| NV2 I     | 150 | 72 | 65 | 48 | 26 | 54  | 73  | 14  |     |    | 6 | kombi |
| NV3C      | 150 | 72 | 65 | 60 | 26 | 54  | 84  | 14  |     |    | 6 | kombi |
| NV3       | 150 | 72 | 65 | 60 | 33 | 65  | 84  | 14  |     |    | 6 | kombi |
| NV4       | 200 | 75 | 66 | 87 | 50 | 100 | 121 | 24  | 150 | 16 | 8 |       |
| NV4a      | 200 | 99 | 87 | 85 | 50 | 95  | 121 | 27  |     |    | 6 |       |
| NV4a SI*  | 200 | 99 | 87 | 85 | 50 | 95  | 121 | 27  |     |    | 6 |       |
| NV1/1000V | 155 | 90 | 87 | 40 | 20 | 45  | 59  | 9   |     |    | 6 |       |

