

MS25-0,63

Mot.protec.circuit breaker



ETI Code:	004600040
Rated operational voltage (AC):	690 V
Setting overl release Ir:	0.4/0.63 A
Current setting range:	0.4/0.63 A
Short-circuit release Irm:	9 A
Catalogue Group:	MS
Max. rated operational voltage (AC):	690 V

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Rated operation power at AC-3, 230 V	0.09 kW
With thermal overload protection	Yes
Overload release current setting(Min)	0.4 A
Rated operating voltage(Max)	440 V
Width	45 mm
Rated permanent current Iu	0.63 A
Rated short-circuit breaking capacity Icu at 400 V, AC	50 kA
Degree of protection (IP)	IP20
Type of control element	Push button
Type of electrical connection of main circuit	Screw connection
Phase failure sensitive	Yes
Number of poles	3
Overload release current setting(Max)	0.63 A
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-3, 400 V	0.12 kW
Rated operating voltage(Min)	230 V
Depth	83 mm
Switch off technique	Thermomagnetic
Height	80 mm

Logistics

Product

Net depth	86.82 mm
Net weight of the product	0.255 kg
Net width	44.7 mm
Net height	83.5 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	0.255 kg
Transport packaging volume	1 dm³
Intermediate packaging weight	12.5 kg
Transport packaging quantity	1 pcs
Intermediate packaging quantity	50 pcs
Customs tariff	85365019
EAN code for a transport packaging	3838733028964
Pallet quantity	1,800 pcs
EAN code for a intermediate packaging	3838895576266

Dimension

