

MPE25-6,3

Mot.protec.circuit breaker



ETI Code:	004648009
Rated operational voltage (AC):	690 V
Setting overl release Ir:	4/6.3 A
Number of poles:	3
IP rating:	IP20
Current setting range:	4/6.3 A
Short-circuit release Irm:	82 A
Catalogue Group:	MPE
Max. rated operational voltage (AC):	690 V

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Rated operation power at AC-3, 230 V	2.2 kW
Overload release current setting(Min)	4 A
Rated operating voltage(Max)	690 V
Rated permanent current Iu	6.3 A
Rated short-circuit breaking capacity Icu at 400 V, AC	100 kA
Degree of protection (IP)	IP20
Adjustment range undelayed short-circuit release(Min)	81.9 A
Type of electrical connection of main circuit	Frame clamp
Phase failure sensitive	Yes
Number of poles	3
Overload release current setting(Max)	6.3 A
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-3, 400 V	2.2 kW
Rated operating voltage(Min)	400 V
Adjustment range undelayed short-circuit release(Max)	81.9 A
Switch off technique	Thermomagnetic

Logistics

Product

Net depth	97.48 mm
Net weight of the product	0.32 kg
Net width	44.8 mm
Net height	97.2 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	7890355188323
Basic packaging weight	0.36 kg
Basic Packaging Dimensions Depth	105 mm
Basic Packaging Dimensions Height	52 mm
Basic packaging volume	0.573 dm ³
Basic Packaging Dimensions Width	105 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	3.71 kg
Transport packaging volume	6.297 dm ³
Transport packaging quantity	10 pcs
Customs tariff	85362010
Transport Packaging Dimensions Height	214 mm
Transport Packaging Dimensions Width	275 mm
Transport Packaging Dimensions Depth	107 mm
EAN code for a transport packaging	17890355188320
Pallet quantity	3,030 pcs

Dimension

