

MPE25-25

Mot.protec.circuit breaker



ETI Code:	004648013
Rated operational voltage (AC):	690 V
Setting overl release Ir:	20/25 A
Number of poles:	3
IP rating:	IP20
Current setting range:	20/25 A
Short-circuit release Irm:	325 A
Catalogue Group:	MPE
Max. rated operational voltage (AC):	690 V

Online product page

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Rated operation power at AC-3, 230 V	11 kW
Overload release current setting(Min)	20 A
Rated operating voltage(Max)	690 V
Rated permanent current Iu	25 A
Rated short-circuit breaking capacity Icu at 400 V, AC	50 kA
Degree of protection (IP)	IP20
Adjustment range undelayed short-circuit release(Min)	325 A
Type of electrical connection of main circuit	Frame clamp
Phase failure sensitive	Yes
Number of poles	3
Overload release current setting(Max)	26 A
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-3, 400 V	11 kW
Rated operating voltage(Min)	400 V
Adjustment range undelayed short-circuit release(Max)	325 A
Switch off technique	Thermomagnetic

Logistics

Product

Net depth	97.48 mm
Net weight of the product	0.32 kg
Net width	44.8 mm
Net height	97.2 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	0.36 kg
Transport packaging volume	0.573 dm³
Transport packaging quantity	1 pcs
Customs tariff	85362010
Transport Packaging Dimensions Height	52 mm
Transport Packaging Dimensions Width	105 mm
Transport Packaging Dimensions Depth	105 mm
EAN code for a transport packaging	7890355188361
Pallet quantity	1,800 pcs

Dimension

