

CEM50.11-230V-50/60Hz

Motor contactor



ETI Code:	004648133
DC rated control supply voltage U_c :	230 V
Rated operation power at AC1:	80 kW
Rated operation current I_e at AC1:	80 A
Rated operation current I_e at AC3, 400V:	50 A
Rated operational voltage (AC):	1,000 V
Rated control circuit voltage U_c (AC):	230 V
Number of poles:	3
No. of aux NO contacts:	1
No. of aux NC contacts:	1
Function:	Motor contactor
Catalogue Group:	CEM Motor contactor

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE

ETIM

Rated control supply voltage AC 60 Hz(Max)	230 V
Rated operation current Ie at AC-3, 400 V	50 A
Voltage type for actuating	AC
Rated control supply voltage AC 60 Hz(Min)	230 V
Rated control supply voltage DC(Min)	230 V
Type of electrical connection of main circuit	Frame clamp
Rated control supply voltage AC 50 Hz(Max)	230 V
Rated control supply voltage AC 50 Hz(Min)	230 V
Number of normally open contacts as main contact	3
Number of auxiliary contacts as normally open contact	1
Rated operation power at AC-3, 400 V	22 kW
Rated control supply voltage DC(Max)	230 V
Number of auxiliary contacts as normally closed contact	1
Rated operation current Ie at AC-1, 400 V	80 A

Logistics

Product

Net depth	116 mm
Net weight of the product	1.105 kg
Net width	69.7 mm
Net height	117.3 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	7894171709441
Basic packaging weight	1.138 kg
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	1.21 kg
Transport packaging volume	1.134 dm³
Transport packaging quantity	1 pcs
Customs tariff	85364900
Transport Packaging Dimensions Height	120 mm
Transport Packaging Dimensions Width	70 mm
Transport Packaging Dimensions Depth	135 mm
EAN code for a transport packaging	7890355108673
Pallet quantity	724 pcs

Dimension

	AC/DC
CEM50	A=116
CEM65	A=116
CEM80	A=116

