

LBS 160 3P

Switch disconnecter



ETI Code:	004661450
Type of Installation:	Base plate mounting
Rated current:	160 A
Number of poles:	3
Thermal current Ith:	160 A
Rated operational current Ie AC-21 A/B at 415V:	160 A
Rated Insulation Voltage:	800 V
Max. rated operational voltage (AC):	415 V
Catalogue Group:	Load Break Switch LBS

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Version as maintenance-/service switch	Yes
Suitable for floor mounting	Yes
Rated permanent current I _n	160 A
Number of poles	3
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-23, 400 V	80 kW
Version as main switch	Yes

Logistics

Product

Net depth	89.6 mm
Net weight of the product	1.11 kg
Net width	140 mm
Net height	135 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	1.11 kg
Transport packaging volume	2.561 dm³
Transport packaging quantity	1 pcs
Customs tariff	85365080
Transport Packaging Dimensions Height	146 mm
Transport Packaging Dimensions Width	179 mm
Transport Packaging Dimensions Depth	98 mm
EAN code for a transport packaging	3838895718833
Pallet quantity	400 pcs