

LBS 400 3P

Switch disconnecter



ETI Code:	004661452
Type of Installation:	Base plate mounting
Rated current:	400 A
Number of poles:	3
Thermal current I _{th} :	400 A
Rated operational current I _e AC-21 A/B at 415V:	400 A
Rated Insulation Voltage:	1,000 V
Max. rated operational voltage (AC):	415 V
Catalogue Group:	Load Break Switch LBS

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Version as maintenance-/service switch	Yes
Suitable for floor mounting	Yes
Rated permanent current I _n	400 A
Number of poles	3
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-23, 400 V	220 kW
Version as main switch	Yes

Logistics

Product

Net depth	132.2 mm
Net weight of the product	4 kg
Net width	230 mm
Net height	235 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	4 kg
Transport packaging volume	13.025 dm³
Transport packaging quantity	1 pcs
Customs tariff	85365080
Transport Packaging Dimensions Height	272 mm
Transport Packaging Dimensions Width	305 mm
Transport Packaging Dimensions Depth	157 mm
EAN code for a transport packaging	3838895718857
Pallet quantity	50 pcs