

LBS 630 3P

Switch disconnecter



ETI Code:	004661453
Type of Installation:	Base plate mounting
Rated current:	630 A
Number of poles:	3
Thermal current I _{th} :	630 A
Rated operational current I _e AC-21 A/B at 415V:	630 A
Rated Insulation Voltage:	1,000 V
Max. rated operational voltage (AC):	415 V
Catalogue Group:	Load Break Switch LBS

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Version as maintenance-/service switch	Yes
Suitable for floor mounting	Yes
Rated permanent current I _n	630 A
Number of poles	3
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-23, 400 V	280 kW
Version as main switch	Yes

Logistics

Product

Net depth	132.1 mm
Net weight of the product	4.363 kg
Net width	230 mm
Net height	235 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	4.363 kg
Transport packaging volume	14.083 dm³
Transport packaging quantity	1 pcs
Customs tariff	85365080
Transport Packaging Dimensions Height	161 mm
Transport Packaging Dimensions Width	308 mm
Transport Packaging Dimensions Depth	284 mm
EAN code for a transport packaging	3838895718864
Pallet quantity	70 pcs