

LBS 1600 3P

Switch disconnecter



ETI Code:	004661457
Type of Installation:	Base plate mounting
Rated current:	1600 A
Number of poles:	3
Thermal current Ith:	1,600 A
Rated operational current Ie AC-21 A/B at 415V:	1600 A
Rated Insulation Voltage:	1,000 V
Max. rated operational voltage (AC):	415 V
Catalogue Group:	Load Break Switch LBS

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Version as maintenance-/service switch	Yes
Suitable for floor mounting	Yes
Rated permanent current I _n	1,600 A
Number of poles	3
Device construction	Built-in device fixed built-in technique
Rated operation power at AC-23, 400 V	710 kW
Version as main switch	Yes

Logistics

Product

Net depth	166 mm
Net weight of the product	12.697 kg
Net width	372 mm
Net height	380.4 mm
Stock unit of measure	pcs

Transport Packaging

Transport packaging weight	12.697 kg
Transport packaging volume	67.883 dm³
Transport packaging quantity	1 pcs
Customs tariff	85365080
Transport Packaging Dimensions Height	295 mm
Transport Packaging Dimensions Width	544 mm
Transport Packaging Dimensions Depth	423 mm
EAN code for a transport packaging	3838895718901
Pallet quantity	15 pcs