


# MLBS 63 4P CO 12VDC

Changeover switch motor op.



|                                                 |                                                    |
|-------------------------------------------------|----------------------------------------------------|
| ETI Code:                                       | 004661650                                          |
| Type (Legacy):                                  | 12VDC                                              |
| Type of Installation:                           | Base plate mounting                                |
| Rated current:                                  | 63 A                                               |
| Type description:                               | 12VDC                                              |
| Number of poles:                                | 4                                                  |
| Thermal current Ith:                            | 63 A                                               |
| Rated operational current Ie AC-21 A/B at 415V: | 63 A                                               |
| Rated Insulation Voltage:                       | 800 V                                              |
| Max. rated operational voltage (AC):            | 690 V                                              |
| Control voltage:                                | 12VDC                                              |
| Catalogue Group:                                | Motorised Change Over Load Break Switch<br>MLBS.CO |

[Online product page](#)

## Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

## ETIM

|                                        |                                   |
|----------------------------------------|-----------------------------------|
| Version as maintenance-/service switch | <b>Yes</b>                        |
| Max. rated operation voltage Ue AC     | <b>415 V</b>                      |
| Suitable for floor mounting            | <b>Yes</b>                        |
| Rated permanent current Iu             | <b>63 A</b>                       |
| Motor drive integrated                 | <b>Yes</b>                        |
| Type of control element                | <b>Toggle</b>                     |
| Number of poles                        | <b>4</b>                          |
| Device construction                    | <b>Complete device in housing</b> |
| Version as main switch                 | <b>Yes</b>                        |

## Logistics

### Product

|                           |                 |
|---------------------------|-----------------|
| Net depth                 | <b>182 mm</b>   |
| Net weight of the product | <b>3.24 kg</b>  |
| Net width                 | <b>235 mm</b>   |
| Net height                | <b>163.4 mm</b> |
| Stock unit of measure     | <b>pcs</b>      |

### Transport Packaging

|                                       |                             |
|---------------------------------------|-----------------------------|
| Transport packaging weight            | <b>3.24 kg</b>              |
| Transport packaging volume            | <b>8.909 dm<sup>3</sup></b> |
| Transport packaging quantity          | <b>1 pcs</b>                |
| Customs tariff                        | <b>85365080</b>             |
| Transport Packaging Dimensions Height | <b>175 mm</b>               |
| Transport Packaging Dimensions Width  | <b>239 mm</b>               |
| Transport Packaging Dimensions Depth  | <b>213 mm</b>               |
| EAN code for a transport packaging    | <b>3838895720164</b>        |
| Pallet quantity                       | <b>120 pcs</b>              |