



NBS-NA 100-630AF AC220/230V

Undervoltage trip unit

ETI Code: 004673221
To use with: NBS 100-630AF
Function accessories: Undervoltage trip NA AC 220/230V

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



CE DECLARATION



EPLAN FILE

ETIM

Rated control supply voltage AC 60 Hz(Max)	230 V
Voltage type for actuating	AC
Rated control supply voltage AC 60 Hz(Min)	230 V
Rated control supply voltage AC 50 Hz(Max)	230 V
Rated control supply voltage AC 50 Hz(Min)	230 V
Type of electric connection	Screw connection

Logistics

Product

Net weight of the product	0.106 kg
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895942504
Basic packaging weight	0.116 kg
Basic Packaging Dimensions Depth	80 mm
Basic Packaging Dimensions Height	39 mm
Basic packaging volume	0.203 dm³
Basic Packaging Dimensions Width	65 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	17.71 kg
Transport packaging volume	26.513 dm³
Intermediate packaging weight	1.152 kg
Transport packaging quantity	150 pcs
Intermediate Packaging Dimensions Height	60 mm
Intermediate packaging quantity	10 pcs
Customs tariff	85389099
Intermediate Packaging Dimensions Width	115 mm
Transport Packaging Dimensions Height	265 mm
Transport Packaging Dimensions Width	290 mm
Transport Packaging Dimensions Depth	345 mm
EAN code for a transport packaging	3838400093424
Pallet quantity	5,550 pcs
EAN code for a intermediate packaging	3838895942511
Intermediate Packaging Dimensions Depth	240 mm