

CS 16 10 PN

Cam switch



ETI Code:	004773164
Type (Legacy):	0-1 IP65
Type of Installation:	Front mounting
Rated current:	16 A
Catalogue Group:	Rotary cam switch in insulated enclosure
Type description:	0-1 IP65
Number of poles:	3
Thermal current Ith:	16 A
Rated operational current Ie AC-21 at 400V:	16 A
Max. rated operational voltage (AC):	400 V
Rated Insulation Voltage:	690 V
Operation:	ON-OFF (0-1) switches in housing with 60° switchin

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Rated permanent current I_u

16 A

Type of control element

Turn button

Type of electrical connection of main circuit

Screw connection

Number of poles

3

Complete device in housing

Yes

With zero (off) position

Yes

Rated operation power at AC-3, 400 V

7.5 kW

Logistics

Product

Net depth	97.3 mm
Net weight of the product	0.195 kg
Net width	65 mm
Net height	82 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895662426
Basic packaging weight	0.195 kg
Basic Packaging Dimensions Depth	76 mm
Basic Packaging Dimensions Height	100 mm
Basic packaging volume	0.76 dm ³
Basic Packaging Dimensions Width	100 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	9.58 kg
Transport packaging volume	3.84 dm ³
Transport packaging quantity	44 pcs
Customs tariff	85363030
Transport Packaging Dimensions Height	20 mm
Transport Packaging Dimensions Width	480 mm
Transport Packaging Dimensions Depth	400 mm
EAN code for a transport packaging	3838895662433
Pallet quantity	924 pcs