

# CS 32 10 PNG

## Cam switch



|                                             |                                                    |
|---------------------------------------------|----------------------------------------------------|
| ETI Code:                                   | 004773166                                          |
| Type (Legacy):                              | 0-1 IP65                                           |
| Type of Installation:                       | Front mounting                                     |
| Rated current:                              | 32 A                                               |
| Catalogue Group:                            | Rotary cam switch in insulated enclosure           |
| Type description:                           | 0-1 IP65                                           |
| Number of poles:                            | 3                                                  |
| Thermal current Ith:                        | 32 A                                               |
| Rated operational current Ie AC-21 at 400V: | 32 A                                               |
| Max. rated operational voltage (AC):        | 480 V                                              |
| Rated Insulation Voltage:                   | 690 V                                              |
| Operation:                                  | ON-OFF (0-1) switches in housing with 60° switchin |

[Online product page](#) 

## Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

## ETIM

|                                               |                  |
|-----------------------------------------------|------------------|
| Rated permanent current Iu                    | 32 A             |
| Type of control element                       | Turn button      |
| Type of electrical connection of main circuit | Screw connection |
| Number of poles                               | 3                |
| Complete device in housing                    | Yes              |
| With zero (off) position                      | Yes              |
| Rated operation power at AC-3, 400 V          | 15 kW            |

## Logistics

### Product

|                           |                  |
|---------------------------|------------------|
| Net depth                 | <b>107.82 mm</b> |
| Net weight of the product | <b>0.35 kg</b>   |
| Net width                 | <b>90.3 mm</b>   |
| Net height                | <b>135.4 mm</b>  |
| Stock unit of measure     | <b>pcs</b>       |

### Basic Packaging

|                                   |                             |
|-----------------------------------|-----------------------------|
| EAN code for a basic packaging    | <b>3838895662464</b>        |
| Basic packaging weight            | <b>0.35 kg</b>              |
| Basic Packaging Dimensions Depth  | <b>111 mm</b>               |
| Basic Packaging Dimensions Height | <b>144 mm</b>               |
| Basic packaging volume            | <b>1.774 dm<sup>3</sup></b> |
| Basic Packaging Dimensions Width  | <b>111 mm</b>               |
| Basic packaging quantity          | <b>1 pcs</b>                |

### Transport Packaging

|                                       |                             |
|---------------------------------------|-----------------------------|
| Transport packaging weight            | <b>7.3 kg</b>               |
| Transport packaging volume            | <b>46.08 dm<sup>3</sup></b> |
| Transport packaging quantity          | <b>18 pcs</b>               |
| Customs tariff                        | <b>85363030</b>             |
| Transport Packaging Dimensions Height | <b>240 mm</b>               |
| Transport Packaging Dimensions Width  | <b>480 mm</b>               |
| Transport Packaging Dimensions Depth  | <b>400 mm</b>               |
| EAN code for a transport packaging    | <b>3838895662471</b>        |
| Pallet quantity                       | <b>378 pcs</b>              |