

CS 25 53 PN

Cam switch



ETI Code:	004773197
Type (Legacy):	1-0-2 IP65
Type of Installation:	Front mounting
Rated current:	25 A
Catalogue Group:	Rotary cam switch in insulated enclosure
Type description:	1-0-2 IP65
Number of poles:	3
Thermal current Ith:	25 A
Rated operational current Ie AC-21 at 400V:	25 A
Max. rated operational voltage (AC):	480 V
Rated Insulation Voltage:	690 V
Operation:	Changeover switches (1-0-2) in housing with 60° sw

[Online product page](#)

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Model	Level switch
Rated permanent current Iu	25 A
Type of control element	Turn button
Type of electrical connection of main circuit	Screw connection
Number of poles	3
Complete device in housing	Yes
With zero (off) position	Yes
Rated operation power at AC-3, 400 V	11 kW

Logistics

Product

Net depth	97.3 mm
Net weight of the product	0.26 kg
Net width	65 mm
Net height	82 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895663133
Basic packaging weight	0.235 kg
Basic Packaging Dimensions Depth	76 mm
Basic Packaging Dimensions Height	100 mm
Basic packaging volume	0.76 dm³
Basic Packaging Dimensions Width	100 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	12.44 kg
Transport packaging volume	46.08 dm³
Transport packaging quantity	44 pcs
Customs tariff	85363030
Transport Packaging Dimensions Height	240 mm
Transport Packaging Dimensions Width	480 mm
Transport Packaging Dimensions Depth	400 mm
EAN code for a transport packaging	3838895663140
Pallet quantity	924 pcs