

CS 40 12 PN2

Cam switch



ETI Code:	004773219
Type (Legacy):	0-Y-D IP65
Type of Installation:	Front mounting
Rated current:	40 A
Catalogue Group:	Rotary cam switch in insulated enclosure
Type description:	0-Y-D IP65
Number of poles:	4
Thermal current Ith:	40 A
Rated operational current Ie AC-21 at 400V:	40 A
Max. rated operational voltage (AC):	480 V
Rated Insulation Voltage:	690 V
Operation:	Star-delta switches in housing

[Online product page](#) 

Documents



TECHNICAL DATA CATALOG



INSTRUCTION MANUAL



CE DECLARATION



2D FILE



3D FILE



EPLAN FILE

ETIM

Model	Star-delta switch
Rated permanent current Iu	40 A
Type of control element	Turn button
Type of electrical connection of main circuit	Screw connection
Number of poles	4
Complete device in housing	Yes
With zero (off) position	Yes
Rated operation power at AC-3, 400 V	18.5 kW

Logistics

Product

Net depth	170.8 mm
Net weight of the product	0.645 kg
Net width	119.6 mm
Net height	160 mm
Stock unit of measure	pcs

Basic Packaging

EAN code for a basic packaging	3838895663850
Basic packaging weight	0.645 kg
Basic Packaging Dimensions Depth	169 mm
Basic Packaging Dimensions Height	186 mm
Basic packaging volume	4.055 dm ³
Basic Packaging Dimensions Width	129 mm
Basic packaging quantity	1 pcs

Transport Packaging

Transport packaging weight	4.87 kg
Transport packaging volume	46.08 dm ³
Transport packaging quantity	6 pcs
Customs tariff	85363030
Transport Packaging Dimensions Height	240 mm
Transport Packaging Dimensions Width	480 mm
Transport Packaging Dimensions Depth	400 mm
EAN code for a transport packaging	3838895663867
Pallet quantity	126 pcs