



Osnovne informacije

Grupa proizvoda	PowerLogic
Tip proizvoda ili komponente	Kondenzator za teške uslove rada
Mrežna frekvencija	50/60 Hz
Ime serije	Zahtevne aplikacije
Sastav harmonika mreže	<= 20 %
Electrical parameters	4,5 Kvar 380 V 50 Hz 5,4 Kvar 380 V 60 Hz 5 Kvar 400 V 50 Hz 6 Kvar 400 V 60 Hz 5,4 Kvar 415 V 50 Hz 6,5 kvar 415 V 60 Hz
Maksimalni dopustivi napon	1.1 x Un (8 časova tokom 24 časa)
Continuous overcurrent capacity	1.8 x In
Nazivni napon	380...415 V AC 50/60 Hz

Dopunske informacije

Dielektrični gubici	< 0.2 W/kvar
Snaga gubitaka	< 0.5 W/kVAr
Tolerancija kapacitivnosti	- 5 % do 10 %
Test napona	2.15 x Un AC između priključaka za 10 s <= 660 V - 3 kV AC između priključka i kućišta za 10 s >= 660 V - 6 kV AC između priključka i kućišta za 10 s
Udarina struja	250 x In
Maksimalni broj preklapanja po godini	7000
Servisni vek u časovima	130000 sati
Dielektrični materijal	Metalizirani polipropilenski sloj sa Zn/Al legurom, specijalna otpornost i profil, specijalna ivica (talasasto sečeno)
Materijal punjenja	Ne PCB suva PUR smola Biorazgradiv
Tip instalacije	Instalacija u zatvorenom
Povezivanje - priključci	Dupli Faston priključak
Način montiranja	Nosač/horizontalno
Prečnik	63 mm
Visina	245 mm
Masa proizvoda	0,9 kg

Okruženje

Standardi	IEC 60831-1 IEC 60831-2
Ip stepen zaštite	IP20
Nadmorska visina za rad	2000 m
Temperaturna klasa	D
Temperatura okoline za rad	-25...55 °C
Relativna vlažnost	95 %

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7,0 cm
Package 1 Width	7,0 cm
Package 1 Length	25,0 cm
Package 1 Weight	1,066 kg
Unit Type of Package 2	S02
Number of Units in Package 2	3
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3,695 kg
Unit Type of Package 3	S04
Number of Units in Package 3	15
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	13,931 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 months
-----------	-----------