

Odvrtlač pneumatski, kompozitni, prihvatač 1/2"

1566



Profil



Opis proizvoda

- 8.000 o/min u slobodnom hodu
- max. obrtni moment: 1223 Nm
- max. obrtni moment pri odvijanju 1756 Nm
- preporučeni pritisak dovoda vazduha: 6,2 bar
- potrošnja vazduha: 113 l/min
- priključak za vazduh: 1/4"

- nivo buke: 93 dB(A)
- za vijke do M24

Prednosti:

- kompozitno kućište
- dvostruki udarni mehanizam TwinHammer
- laka i brza promena smera jednom rukom
- kompaktan i snažan
- sa regulatorom za 3 različite brzine zavrtnja/odvrtanja

Upotreba:

- auto-industrija
- avio-industrija
- poljoprivredna mehanizacija
- teška industrija
- veće građevinske mašine
- brodogradnja
- individualna montaža


VAŽNO!

- UVEK koristite Uniorove IMPACT nasadne ključeve i pribor

		L	A	B		
627570	1/2"	187	70	193	1223	2227

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Upotreba (slike)



Slika (slike)



Dodatna oprema



Spojnica muška



Spojnica muška



Spojnica ženska



Spojnica ženska



Pripremna grupa za pneumatski alat 3/8"



Pripremna grupa za pneumatski alat 1/2"



Crevo spiralno za vazduh

Pravilna upotreba



- The pressure in the tool during the operation has to be at least 6.2 bar for the tool to work properly.
- Regularly clean and dry the air filters and inlet air supply.
- Always use clean and dry air with the correct mixture of oil, for maximum tool life.
- Check the joints and ensure that the tubes and other equipment are not damaged before use.
- All tools should be gently oiled prior to being stored.
- Always store pneumatic tools in dry places away from water.
- Always use original spare parts.
- Repairs can be performed only by authorised staff people authorised by Unior d.d.



- Always disconnect tools not in use from the air supply.