

Moment ključ industrijski, prihvatač 3/4"

265



Profili



Standardi

ISO 6789

Opis proizvoda

- robusna izrada, daje tačne rezultate, do +/-4%, čak i u vrlo teškim uslovima rada
- svaki ključ se isporučuje sa atestom o kalibraciji, u skladu sa ISO 9000: 2000
- velikom preciznošću pomaka smanjuje se mogućnost pretezanja
- zupčasti mehanizam ključa omogućava kontrolisani moment koji neće dovesti do preteranog zatezanja vijka
- delovanje obrtnog momenta: u oba smera, ali uvek koristite smer koji je trenutno podešen na drški moment ključa
- za vijke sa desnim i levim navojem
- dvojna skala (Nm i lbf.ft)
- izrađen prema standardu ISO 6789


Upotreba:

- poljoprivredna mehanizacija
- građevinarstvo
- teška industrija
- veće građevinske mašine

- brodogradnja
- avio-industrija
- Ne koristite moment ključ za odvijanje!

VAŽNO!



- Ne koristite moment ključ za odvijanje!
- Alat se mora koristiti sa ravnomernim pritezanjem (jednaka pomeranja) i u skladu sa uputstvom za upotrebu
- Moment ključ vrši pritezanje samo u smeru prikazanom na nalepnici ključa, i ona označava ispravan smer pritezanja!
- Predviđeni period za rekalkibraciju moment ključa je 12 meseci ili približno 5.000 merenja od dana kupovine.
- UVEK podesite merni mehanizam na početnu poziciju nakon upotrebe.
- Kada postignete željeni moment, nije potrebno dalje pritezanje.
- Moment ključ može biti oštećen ukoliko se ne poštuje uputstvo za upotrebu.




					
616802	3/4"	200 - 800	150 - 600	1140	9000
616803	3/4"	300 - 1000	200 - 750	1470	9800

* Fotografije proizvoda su simbolične. Sve dimenzije su u mm, a težina u gramima. Sve navedene dimenzije mogu odstupati u granicama tolerancija.

Upotreba (slike)





Slika (slike)



Povezani proizvodi



Moment ključ



Moment ključ

Bezbednost (slike)

