

TRI-MATIC



Characteristics

- Impact-resistant ABS plastic housing
- Handy, compact case design
- Exact 2-piece tape brake for precise inner measuring
- Shock absorber system for a gentle tape stop
- Long-lasting precision and protection against damage thanks to a reinforced initial tape section
- Robust steel belt clip for secure hold

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Model	Length	Tape width	PU	VP	Art. Nr.	EAN
TM 3	3 m	13 mm/m	6		50023201	9002719002741
TM 5	5 m	19 mm/m	6		50023301	9002719003151
TM 8	8 m	25 mm/m	6		50023401	9002719003168
TM 10	10 m	25 mm/m	6		50023501	9002719008934
TM 3	3 m	13 mm/m	1		50023701	9002719010241
TM 5	5 m	19 mm/m	1		50023801	9002719010289



Technical details

Item description	Tape measure
Graduations	mm
EC accuracy class	I
Tape material	Steel
Tape surface	matt lacquered, yellow
End hook	Stainless steel, sliding
Tape brake	Brake, 2-piece
Rivets for end hooks	2
Retraction damping end hook	Shock absorber
Reinforcement plate	Stainless steel
Housing material	ABS
Housing color	chrome-plated
Belt clip	Stainless steel
Replacement tape	upon request

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götzis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch