

VITO CONCRETE PAINT

Water-Based Paint for Concrete surfaces

Water-based acrylic masonry paint for exterior use. Due to its excellent resistance to alkalis, it is recommended for the painting and protection of all concrete surfaces. It offers high coverage and spreading rate. Easy application and excellent levelling for a smooth matt finish.



Advantages:

- High coverage and excellent spreading rate
- Excellent workability and easy application
- Available in anthracite shade

PRODUCT FEATURES

TECHNICAL CHARACTERISTICS



Viscosity

110 ± 10 KU (ASTM D 562, 25°C)

Density

1,47 ± 0,02 Kg / L (ISO 2811)

Gloss


< 5 units @ 60° (ISO 2813)

FINISH

Mat	Satin	Gloss
✓		
Mat Finish		

COLOURS

Available in anthracite shade 985.



COVERAGE



One coat

10-12 m²/L

Two coats

5-6 m²/L

DILUTION



Water

8-10 %

DRYING TIME



Touch dry

30-60 min

Recoat

3-4 h

PACKAGING

Anthracite	750 mL	3 L	9 L
------------	--------	-----	-----



APPLICATION

APPLICATION FIELD

For any cement surface.

PREPARATION



Surfaces should be smooth, clean and dry, free from grease, dust, loose or flaking paint.
To fill any cracks or holes use Acrylic Putty.



Old surfaces previously covered with water paints or distempers (lime wash or ceiling white) should be primed with with Acrylan Unco Eco, Durovit or Vitosin.



New surfaces made of plaster, concrete, cement, plasterboard, etc. should be first primed with Acrylan Unco Eco.

STEPS

- 1 Dilute 8-10% with water and stir well before use.
- 2 Apply the first coat by brush, roller or airless spray gun.
- 3 Recoat after 3-4 hours.

TIPS

- Application at 5-35°C and <70% RH. Don't apply if there is a risk of rain/frost in the next 48 hours.
- Allow new concrete surfaces to cure a minimum of 30 days prior to paint application.
- Allow at least 3 weeks before cleaning and washing newly painted surfaces

with Vito Concrete Paint. Wash gently with water using a soft sponge. In case of tough stains, use a mild colourless detergent or soapy water.

- Tools must be cleaned immediately after use with water and if needed, with soapy water or detergent.
- Minimize paint wastage by estimating

how much paint you will need.

- Recover unused paint for re-use. After paint application, seal the container and store it for future use.
- Do not dispose of liquid waste into ground water table. Unused paint requires special handling for safe disposal.

ADDITIONAL INFORMATION

VOCs (Volatile Organic Compounds)



"Exterior walls of mineral substrate". VOC content limit **40 g/L**. Maximum VOC content **39 g/L** VOCs (ready for use product).

PRECAUTIONS



Please read carefully the labelling mentioned on the can before use. For detailed instructions on hazards and safety in use the Safety Data Sheet is available upon request. Poisons Control Centre Tel. : +30 210 7793 777

STORAGE



5°C-38°C
Keep containers closed in a cool and dry area.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

