

HYROOF POLYESTER REINFORCEMENT

HyRoof Polyester Reinforcement is an effective tool for enhancing and improving the efficiency of the HyRoof Hybrid PU Waterproofing System.

Advantages:

- Anti-allergenic
- Rot-proof
- Resistant to atmospheric agents
- Excellent adaptability



PRODUCT FEATURES


TECHNICAL CHARACTERISTICS



It is a specially designed polyester reinforcement (weight 50-75gr / m²). Due to its flexibility, it adapts easily to the surface to be treated, while its high permeability enables it to merge perfectly with the liquid waterproofing material.

PACKAGING

Available in rolls of 1X100m



APPLICATION

APPLICATION PROCEDURE



After applying a layer of HyRoof Hybrid PU material, lay the reinforcement which is incorporated while the layer of the waterproofing material is still wet and then apply a second layer of HyRoof Hybrid PU.

The above technical data, information and instructions are based on our long experience and laboratory tests and are intended only to describe the product and determine its application. However, the end user should check the suitability of the product for its intended use. Our company guarantees the quality of the product itself, and in any case bears no responsibility for any damage or damage caused if the product is not used properly and in accordance with its instructions for use. The company has the right to revise this technical data sheet without any prior notice.

+30.210.5589.400
TECHNICAL SUPPORT

