

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ

PRODUCT CODE
ŠIFRA PROIZVODA

131301



TEHNIČKI PODACI

Jednoručna baterija
Uzidna montaža
Masivna konstrukcija
Keramički mešač KEROX® 35 HWS
Automatski prebacivač
NEOPERL® PERLATOR® COINSLOT®
Klasa protoka 9lit/min na tušu
Tuš ruža D.220mm sa zglobovom

TECHNICAL DETAILS

Single lever mixer
Built-in the wall
Solid construction
Ceramic cartridge KEROX® 35 HWS
Automatic diverter
Aerator NEOPERL® PERLATOR® COINSLOT®
Flow rate 9 lit/min on shower
Shower rose D.220mm with knob

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

