

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# STOLZ

PRODUCT CODE  
ŠIFRA PROIZVODA

**131401**



### TEHNIČKI PODACI

Jednoručna baterija  
Uzidna montaža  
Masivna konstrukcija  
Keramički mešač KEROX® 35 HWS  
Klasa protoka Z - 7 lit/min  
NEOPERL® PERLATOR® COIN SLOT®

### TECHNICAL DETAILS

Single lever mixer  
Built-in the wall  
Solid construction  
Ceramic cartridge KEROX® 35 HWS  
Flow class Z - 7 lit/min  
Aerator NEOPERL® PERLATOR® COIN SLOT®

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

