

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ THERMO

COLLECTION
SERIJA

PRODUCT CODE
ŠIFRA PROIZVODA

1T32120



TEHNIČKI PODACI

Termostatska baterija
Zidna montaža
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
PKMTH2 mešač
Keramički gornji deo
Heavy Duty ekscentar kolena
Hromirane rozete
Pokretni izliv 200mm

TECHNICAL DETAILS

Thermostatic mixer
Wall mounted
Flow class Z - 7 lit/min
NEOPERL® PERLATOR® HONEYCOMB
PKMTH2 thermostatic cartridge
Ceramic head part
Heavy Duty eccentric connectors
Chromed rossetes
Swivel spout 200mm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

