

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STOLZ THERMO

PRODUCT CODE
ŠIFRA PROIZVODA

1T37252



TEHNIČKI PODACI

Termostatska baterija
Zidna montaža
Regulacija protoka do 5 lit/min na tušu
PKMTH2 mešač
Podesivi usponski tuš
Ručni prebacivač
Zglobna tuš ruža 250x250 mm
Duplo pleteno tuš crevo 1.5m
Easy Clean tuš ručica
Heavy Duty ekscentar kolena
Hromirane rozete

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Thermostatic mixer
Wall mounted
Flow regulation on shower up to 5 lit/min
PKMTH2 thermostatic cartridge
Adjustable height stand pipe shower
Manual diverter
Shower head 250x250 mm
Double lock shower hose 1.5m
Easy Clean hand shower
Heavy Duty eccentric connectors
Chromed rossetes

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

