

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 GOLD

PRODUCT CODE
ŠIFRA PROIZVODA

230301G



TEHNIČKI PODACI

Dvoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD brušeno zlato
Montiranje na tri otvora
Klasa protoka Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR® PPM24SA
Keramički gornji deo
Set za pričvršćenje
Priključni cev

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Two handle mixer
Minimalist design
Solid brass body
Brushed gold PVD finish
Three hole mounted
Flow rate Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
Ceramic head parts
Single screw fixing set
Connecting hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

