

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

230401B



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - Matt black
Montiranje na dva otvora
Klasa protoka Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR® PPM24SA
Keramički mešač CITEC® 25mm PKM25SA
Set za pričvršćenje
NEOPERL® SPX® priključna creva FB50PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Matt black finish
Two hole mounted
Flow rate Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
CITEC®25 mm ceramic cartridge - PKM25SA
Fixing set
NEOPERL® SPX® connecting hoses - FB50PX

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

