

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

231603



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Uzidna baterija
Automatski prebacivač za tuš
Tuš ruža D.300mm - PTRUSP12
Keramički mešač KEROX® 35mm - PKM35A
SILVERFLEX tuš crevo 170cm - PGC170SF
Tuš ručica 3 Funkcije - PTR3C12

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Build in the wall
Automatic shower diverter
Shower head D.300mm - PTRUSP12
KEROX®35 mm ceramic cartridge - PKM35A
SILVERFLEX shower hose 170cm - PGC170SF
3 Function hand shower - PTR3C12

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C