

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

231603B



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - Matt black
Uzidna baterija
Automatski prebacivač za tuš
Tuš ruža 210x210mm - PTRUSP5D
Keramički mešač KEROX® 35mm - PKM35A
DARKFLEX tuš crevo 150cm - PGC150DF
Tuš ručica 3 Funkcije - PTR3C13D

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Matt black finish
Build in the wall
Automatic shower diverter
Shower head 210x210mm - PTRUSP5D
KEROX®35 mm ceramic cartridge - PKM35A
DARKFLEX shower hose 150cm - PGC150DF
3 Function hand shower - PTR3C13D

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C