

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

231907



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Uzidna baterija
Keramički prebacivač Turn4
Keramički mešač KEROX® 35mm - PKM35A
NEOPERL® HYBRID prebacivač- PREB133
NEOPERL®COINSLOT® - PPM24CS

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Build in the wall
Ceramic Turn4 diverter cartridge
KEROX®35 mm ceramic cartridge - PKM35A
NEOPERL® HYBRID shower diverter - PREB133
NEOPERL®COINSLOT® - PPM24CS

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C