

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

233204



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Montaža na rub kade
Keramički prebacivač 90°
NEOPERL®HONEYCOMB® - PPM28N
Keramički mešač KEROX® 35mm - PKM35A
Tuš crevo STOLZ 200cm - PGC20015
Tuš ručica 3 Funkcije - PTR3C13

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Bath tub rim assembly
Ceramic diverter 90°
NEOPERL®HONEYCOMB® - PPM28N
KEROX®35 mm ceramic cartridge - PKM35A
STOLZ shower hose 200cm - PGC20015
3 Function hand shower - PTR3C13

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C