

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

237351



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Zidna montaža
Keramički prebacivač 180°
Tuš ruža 200*300mm - PTRUSP16
Keramički mešač CITEC® 25mm - PKM25SB
SILVERFLEX tuš crevo 170cm - PGC170SF
Tuš ručica 3 Funkcije - PTR3C13
Protok max. 8lit/min - WaterCare

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Wall assembly
Ceramic diverter 180°
Shower head 200*300mm - PTRUSP16
CITEC®25 mm ceramic cartridge - PKM25SB
SILVERFLEX shower hose 170cm - PGC170SF
3 Function hand shower - PTR3C13
WaterCare - max flow rate 8lit/min

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C