

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

238401



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Fiksiranje na jedan otvor
Keramički mešač CITEC® 25mm - PKM25SC
Mešač sa H-V pozicijom
Set za pričvršćenje sa jednim vijkom
Pokretni izliv 360°
NEOPERL® SPX® priključna creva - FB50PX
Izvlačni tuš AMFAG® MICRO67 - PTR385S2

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Chrome finish
Single hole assembly
CITEC® 25 mm ceramic cartridge - PKM25SC
Cartridge with H-V positioning
Single screw fixing set
360° swivel spout
NEOPERL® SPX® connecting hoses - FB50PX
AMFAG® MICRO67 - pull-shower - PTR385S2

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C