

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

238401B



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - Matt black
Fiksiranje na jedan otvor
Keramički mešač CITEC® 25mm - PKM25SC
Mešač sa H-V pozicijom
Set za pričvršćenje sa jednim vijkom
Pokretni izliv 360°
NEOPERL® SPX® priključna creva - FB50PX
Izvlačni tuš AMFAG® MICRO67 - PTR385S2

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Matt black finish
Single hole assembly
CITEC® 25 mm ceramic cartridge - PKM25SC
Cartridge with H-V positioning
Single screw fixing set
360° swivel spout
NEOPERL® SPX® connecting hoses - FB50PX
AMFAG® MICRO67 - pull-shower - PTR385S2

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C