

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2

PRODUCT CODE  
ŠIFRA PROIZVODA

## 238501



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Hromirana završna obrada  
Fiksiranje na jedan otvor  
Keramički mešač CITEC® 25mm - PKM25SC  
Mešač sa H-V pozicijom  
Set za pričvršćenje sa jednim vijkom  
Pokretni izliv 360°  
NEOPERL® SPX® priključna creva - FB50PX  
Izvlačni tuš AMFAG® MICRO67 - PTR385S2

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Chrome finish  
Single hole assembly  
CITEC® 25 mm ceramic cartridge - PKM25SC  
Cartridge with H-V positioning  
Single screw fixing set  
360° swivel spout  
NEOPERL® SPX® connecting hoses - FB50PX  
AMFAG® MICRO67 - pull-shower - PTR385S2

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C