

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 BLACK

PRODUCT CODE
ŠIFRA PROIZVODA

238603B



TEHNIČKI PODACI

Jednoručna baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - Matt black
Otvorena veza bojler-baterija
Smanjeni protok 3 - 5 lit/min
Usmerivač NEOPERL® NEOSTRAHL® FS Dripless
Keramički mešač KEROX® 35 NDO HWS
INOX set za pričvršćenje
IMQ sertifikovana fleksibilna priključna creva
Tuš ručica PTR386JD
Pleteno izvlačno tuš crevo PGC385JC

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Minimalist design
Solid brass body
Matt black finish
Open flow waterheater-mixer
Reduced flow rate 3 - 5 lit/min
Jet breaker NEOPERL® NEOSTRAHL® DRIPLESS FS
Ceramic cartridge KEROX® 35 NDO HWS
Stainless Steel rapid instalation set
IMQ certified flexible connection hoses
Pull-out shower PTR386JD
Braided pull-out shower hose PGC385JC

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C