

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# S2 GOLD

PRODUCT CODE  
ŠIFRA PROIZVODA

**238603G**



### TEHNIČKI PODACI

Jednoručna baterija  
Minimalistički dizajn  
Telo od mesinga  
Završna obrada - PVD Dark black  
Otvorena veza bojler-baterija  
Smanjeni protok 3 - 5 lit/min  
Usmerivač NEOPERL® NEOSTRAHL® FS Dripless  
Keramički mešač KEROX® 35 NDO HWS  
INOX set za pričvršćenje  
IMQ sertifikovana fleksibilna priključna creva  
Tuš ručica PTR386G  
Pleteno izvlačno tuš crevo PGC385JC

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Minimalist design  
Solid brass body  
Brushed gold PVD finish  
Open flow waterheater-mixer  
Reduced flow rate 3 - 5 lit/min  
Jet breaker NEOPERL® NEOSTRAHL® DRIPLESS FS®  
Ceramic cartridge KEROX® 35 NDO HWS  
Stainless Steel rapid instalation set  
IMQ certified flexible connection hoses  
Pull-out shower PTR386G  
Braided pull-out shower hose PGC385JC

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C