

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2 B&G

PRODUCT CODE
ŠIFRA PROIZVODA

254101BG



TEHNIČKI PODACI

Ventil za hladnu vodu
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD Dark black
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
Kermički uložak KCG® 25mm -PKM25A
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključno crevo- FB50PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Cold water tap
Minimalist design
Solid brass body
Dark black PVD finish
Single hole assembly
Flow rate Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
KCG®25 mm ceramic cartridge - PKM25A
Single screw fixing set
NEOPERL® SPX® connection hose- FB50PX

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

