

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

254209



TEHNIČKI PODACI

Ventil za hladnu vodu
Minimalistički dizajn
Telo od mesinga
Hromirana završna obrada
Montiranje na jedan otvor
Klasa protoka Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
Kermički uložak KCG® 25mm -PKM25A
Set za pričvršćenje sa jednim vijkom
NEOPERL® SPX® priključno crevo- FB60PX

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Cold water tap
Minimalist design
Solid brass body
Chrome finish
Single hole assembly
Flow rate Z - 7 lit/min
NEOPERL® SLIMAIR® SLC® SSR®- PPM24SA
KCG®25 mm ceramic cartridge - PKM25A
Single screw fixing set
NEOPERL® SPX® connection hose- FB60PX

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C