

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

Thermo S2

PRODUCT CODE
ŠIFRA PROIZVODA

2T37101B



TEHNIČKI PODACI

Termostatska baterija
Minimalistički dizajn
Telo od mesinga
Završna obrada - PVD Dark black
Zidna montaža
Keramički gornji deo
Termostatski uložak AP - PKMTH2
DARKFLEX tuš crevo 150cm - PGC150DF
Tuš ručica 3 Funkcije - PTR3C13D

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Thermo regulation mixer
Minimalist design
Solid brass body
Dark black PVD finish
Wall assembly
Ceramic head part
Theromostatic cartridge AP - PKMTH2
DARKFLEX shower hose 150cm - PGC150DF
3 Function hand shower - PTR3C13D

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C