

SPECIFICATION SHEET

TEHNIČKI LIST



STOLZ

COLLECTION
SERIJA

S4

PRODUCT CODE
ŠIFRA PROIZVODA

453130B



TEHNIČKI PODACI

Ventil za hladnu vodu

Montiranje na jedan otvor

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

Pokretni izliv

Flühs® LIFETIME keramički gornji delovi PGD9112

Matt black rozeta

TECHNICAL DETAILS

Cold water tap

Single hole mounted

NEOPERL® PERLATOR® Coin Slot PCA® PPM21CS

Swivel spout

Flühs® LIFETIME ceramic head parts PGD9112

Matt black rossette

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

ROSAN