

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

SMART

PRODUCT CODE
ŠIFRA PROIZVODA

JA321002



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Klasa protoka Z - 7 lit/min
NEOPERL® PERLATOR® COIN SLOT®
Keramički mešač KEROX® 35
Heavy Duty ekscentar kolena
Polirane Inox rozete
Pokretni izliv 200mm

TECHNICAL DETAILS

Single lever mixer
Attached to the wall
Flow rate Z - 7 lit/min
NEOPERL® PERLATOR® COIN SLOT®
Ceramic cartridge KEROX® 35
Heavy Duty eccentrics
Polished SS304 rosettes
Swivel spout 200mm

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

