

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

SMART

PRODUCT CODE
ŠIFRA PROIZVODA

JA371001



TEHNIČKI PODACI

Jednoručna baterija
Zidna montaža
Keramički mešač KEROX® 35
Polirane Inox 304 rozete
Heavy Duty ekscentar kolena
Duplo pleteno tuš crevo 1.5m
Easy Clean tuš ručica
Fiksni držač tuša

TECHNICAL DETAILS

Single lever mixer
Attached to the wall
Ceramic cartridge KEROX® 35
Polished SS304 rosettes
Heavy Duty eccentrics
Double lock shower hose 1.5m
Easy Clean hand shower
Shower wall support

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

