

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

B/2

PRODUCT CODE
ŠIFRA PROIZVODA

JB31701



TEHNIČKI PODACI

Jednoručna baterija
Montaža u zidu
Klasa protoka C - na izlivu
Regulacija protoka do 5 lit/min na tušu
Keramički mešač KEROX® 35 HWS
Hromirana rozeta u ravni sa zidom
Automatski prebacivač za tuš na telu
Automatski prebacivač na izlivu
Konzola tuša L. 400mm
Zglobna tuš ruža D. 220mm
Easy Clean tuš ručica
Duplo pleteno tuš crevo 1.5m

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Built-in wall
Flow class C - on spout
Flow regulation on shower up to 5 lit/min
Ceramic cartridge KEROX® 35 HWS
Chromed minimalistic rossete
Automatic shower diverter on mixer body
Automatic diverter on the spout
Shower colum L. 400mm
Shower head D. 220mm
Easy Clean hand shower
Double lock shower hose 1.5m

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

